

U.S. DEPARTMENT OF LABOR  
Occupational Safety and Health AdministrationForm Approved  
OMB No. 44-R1387

MAR 6 1982

## MATERIAL SAFETY DATA SHEET FEB 02 1982

## SECTION I

MANUFACTURER'S NAME Ellis Paint Company	EMERGENCY TELEPHONE NO. (213) 261-0645
ADDRESS (Number, Street, City, State, and ZIP Code) 3150 E. Pico Blvd., Los Angeles, Calif. 90023	
CHEMICAL NAME AND SYNONYMS	TRADE NAME AND SYNONYMS 759- (C-759 Beige)
CHEMICAL FAMILY Vinyl Acrylic Copolymer	FORMULA

## SECTION II - HAZARDOUS INGREDIENTS

PAINTS, PRESERVATIVES, & SOLVENTS	%	TLV (Units)	ALLOYS AND METALLIC COATINGS	%	TLV (Units)
PIGMENTS	38		BASE METAL		
CATALYST			ALLOYS		
VEHICLE	14		METALLIC COATINGS		
SOLVENTS	48		FILLER METAL PLUS COATING OR CORE FLUX		
ADDITIVES			OTHERS		
OTHERS					
HAZARDOUS MIXTURES OF OTHER LIQUIDS, SOLIDS, OR GASES				%	TLV (Units)

## SECTION III - PHYSICAL DATA

BOILING POINT (°F.)	212	SPECIFIC GRAVITY (H <sub>2</sub> O=1)	1.4
VAPOR PRESSURE (mm Hg.)	Like Water	PERCENT VOLATILE BY VOLUME (%)	Water 68
VAPOR DENSITY (AIR=1)	Like Water	EVAPORATION RATE (Bu AC =1)	Like Water
SOLUBILITY IN WATER	soluble		
APPEARANCE AND ODOR	Beige liquid with a sweet smell		

## SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT (Method used)	Non-Flammable	FLAMMABLE LIMITS	Lel	Uel
			NA	NA
EXTINGUISHING MEDIA	NA			
SPECIAL FIRE FIGHTING PROCEDURES	NA			
UNUSUAL FIRE AND EXPLOSION HAZARDS	NA			

### SECTION V - HEALTH HAZARD DATA

THRESHOLD LIMIT VALUE	NA
EFFECTS OF OVEREXPOSURE	Repeated skin contact may cause mild irritation
EMERGENCY AND FIRST AID PROCEDURES	Move subject to fresh air, flush eyes with a large amount of water for (15) minutes and consult a physician. If irritation persists wash skin with soap and water.

### SECTION VI - REACTIVITY DATA

STABILITY	UNSTABLE		CONDITIONS TO AVOID	N.A.
	STABLE	X		
INCOMPATIBILITY (Materials to avoid)				
HAZARDOUS DECOMPOSITION PRODUCTS Thermal Decomposition may yield oxides of carbon				
HAZARDOUS POLYMERIZATION	MAY OCCUR		CONDITIONS TO AVOID	NA
	WILL NOT OCCUR	X		

### SECTION VII - SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED	Absorb spill with inert material (dry sand, earth) and transfer to a suitable container for disposal.
WASTE DISPOSAL METHOD	Incinerate liquid in approved equipment according to local, State and Federal regulations.

### SECTION VIII - SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION (Specify type) None required in course of normal operation		
VENTILATION	LOCAL EXHAUST	SPECIAL
	MECHANICAL (General)	OTHER
PROTECTIVE GLOVES	Impervious gloves	EYE PROTECTION
		Splash-proof goggles
OTHER PROTECTIVE EQUIPMENT		
Eye wash facility, emergency shower		

### SECTION IX - SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING	Keep from freezing
OTHER PRECAUTIONS	